



2 000h



Dimmable

## General Data

Article No.	24315704
Code	ITT 300W 235V-0170 K R7S
Product EAN	4008597157042
Customs tariff no.	85394900
Box quantity (pcs.)	20
EAN Box	4008597457043
Gross weight of box in kg	0.318
Length of box in m	0.14
Width of box in m	0.11
Height of box in m	0.08
ETIM class	EC002963
ETIM class name	IR lamp
Product status	 Phase Out

## Electric Parameters

Lamp power	300 W
Weighted energy consumption in 1,000 hours	300 kWh
Lamp voltage	235-235 V

## Electric Parameters

Lamp voltage	235-235 V
Lamp voltage	235-235 V
Nominal current (A)	1,3 A

## Service Life

Average nominal lifespan	2000 h
--------------------------	--------

## Specification

Diameter lamp	10 mm
Length max.	120 mm
Total length	119.6 mm
Contact distance l	114.2 mm
Lamp shape	Other
Socket	Other

## Miscellaneous

EU-date of phase-out	01.09.2021
EU-phase out, important additional information	no exception due to length
EU Directive	Ecodesign directive 2019/2020

## Notes

Highly efficient infrared lamp for mains voltage 230V, double ended, controllable, long service life, no ramp-up-time - quick heating up

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

## Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent and halogen lamps emit a continuous red-dominated spectrum of electromagnetic radiation as it is generated by heating up a tungsten filament. The wavelength range of visible light reaches from 380 to 780 nm, above (longer wavelength) there is infrared radiation which can be used for targeted heat generation.

The addition of halogens to the filling gas enhances the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or specific coating.

## General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or

# Ralotherm Infrared Lamp 0170 R7s

ITT 300W 235V-0170 K R7S

# Radium

even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.