



## Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

## Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Application	Stage & Studio
Product Remark	- Lamp also available in 240 V model.

#### Electrical data

Type of Current	AC
-----------------	----

#### Light technical data

Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm

#### Physical attributes

Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	6-C8
Reflector Coating	19.00

#### Additional product data

Operating Position	Any
Class	C (gas)

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	4050300654201	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
	4050300654218	Shipping box (Case)	12	6.9 in x 5.8 in x 5.7 in	2.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.