



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Application	Projector, Microfilm, Microscope, Studio
LIF Code	M/184
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Type of Current	AC
-----------------	----

Light technical data

Light Center Length - LCL (in)	1.248 in
Light Center Length - LCL (mm)	32 mm



Physical attributes

Maximum Overall Length (in)	1.950 in
Maximum Overall Length (mm)	50 mm
Length l (in)	1.950 in
Length l (mm)	50 mm
Diameter d (in)	0.433 in
Diameter d (mm)	11.00 mm
Distance a (in)	1.248 in
Distance a (mm)	32 mm
Filament Dimensions Length (in)	0.1250 in
Filament Dimensions Length (mm)	3.2 mm
Filament Dimensions Width (in)	0.234 in
Filament Dimensions Width (mm)	6 mm
Reflector Coating	11.00

Additional product data

Operating Position	s 90
Class	C (gas)

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	4050300012025	Folding box (SKU)	1		
	4050300992129	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.