

64641 HLX

Low-voltage halogen lamps without reflector



Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



Product datasheet

Technical data


Product information

Order reference	64641 HLX
-----------------	-----------

Electrical data

Nominal voltage	17.0 V
Nominal wattage	150.00 W

Dimensions & weight



Diameter	11.5 mm
Length	50.0 mm
Light center length (LCL)	32.0 mm
Filament length	3.00 mm
Illuminated field	3.0*6.0 mm ²
Filament diameter	6.0 mm

Lifespan

Lifespan	2000 h
----------	--------

Additional product data

Base (standard designation)	G6.35
Minimum diameter of lamp enclosure	14 mm

Capabilities

Burning position	s135
Application	Other

Country specific categorizations

Product datasheet

Order reference	64641 HLX
------------------------	-----------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4050300048260 4055462170156 4055462170187
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300048260	OSRH64641HLX	-	-	-
4050300048260	OSRH64641HLX	-	-	-