

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Application	AIRCRAFT, FIBER-OPTIC, MICROSCOPE
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Type of Current	AC
-----------------	----

Light technical data

Light Center Length - LCL (in)	0.702 in
Light Center Length - LCL (mm)	18 mm



Physical attributes

Maximum Overall Length (in)	1.872 in
Maximum Overall Length (mm)	48 mm
Length l (in)	1.872 in
Length l (mm)	48 mm
Length l max. (in)	1.872 in
Length l max. (mm)	48 mm
Diameter d (in)	0.472 in
Diameter d (mm)	12.00 mm
Distance a (in)	0.702 in
Distance a (mm)	18 mm
Filament Dimensions Length (in)	0.1050 in
Filament Dimensions Length (mm)	2.7 mm
Filament Dimensions Width (in)	0.183 in
Filament Dimensions Width (mm)	4.7 mm

Additional product data

Operating Position	s 90
Class	C (gas)

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	4050300535531	Folding box (SKU)	1	2.8 in x 0.7 in x 1.1 in	
	4050300535548	Shipping box (Case)	30	6.2 in x 3.2 in x 5.2 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.