

64654 HLX 250W 24V 12/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54304
Product Name	64654HLX 24V 12/CS 1/SKU
Ordering Abbreviation	64654 HLX 250W 24V 12/CS 1/SKU
Brand Name	OSRAM
General Description	250 WATT, TUNGSTEN HALOGEN, LOW VOLTAGE WITHOUT REFLECTOR
Application	Projector, Microfilm, Microscope, Studio
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	250 W
Nominal Voltage	24 V
Type of Current	AC

Light technical data

Luminous Flux	9000 lm
Light Center Length - LCL (in)	1.365 in
Light Center Length - LCL (mm)	35 mm
Color Temperature	3450 K
Color Rendering Index	100
Average Rated Life	300 h

Physical attributes



Base	GY9.5 BIPIN
Bulb Shape	T13,5
Maximum Overall Length (in)	2.677 in
Maximum Overall Length (mm)	68 mm
Length l (in)	2.677 in
Length l (mm)	68 mm
Diameter d (in)	0.591 in
Diameter d (mm)	15.00 mm
Distance a (in)	1.365 in
Distance a (mm)	35 mm
Filament Dimensions Length (in)	0.1560 in
Filament Dimensions Length (mm)	4 mm
Filament Dimensions Width (in)	0.312 in

Product datasheet

Filament Dimensions Width (mm)	8 mm
Reflector Coating	15.00

Additional product data

Operating Position	s 90
Class	C (gas)
Lamp Type	HLX



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54304	4008321241399	Folding box (SKU)	1	1.7 in x 1.7 in x 4.4 in	
54304	4008321241405	Shipping box (Case)	12	7.1 in x 5 in x 5.5 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.