

## 64333 A 40-15

Halogen lamps with reflector, current-controlled, 30...40 W



### Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

### Product family features

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions



# Product datasheet

## Technical data

### Product information

Order reference	64333
-----------------	-------


### Electrical data

Lamp current	6.6 A
Nominal wattage	40.00 W

### Photometrical data

Luminous intensity	10000 cd
Axial luminous intensity	12700 cd
Color rendering index Ra	100

### Dimensions & weight



Diameter	35.3 mm
Length	35.0 mm
Length with base excl. base pins/connection	37.00 mm

### Lifespan

Lifespan	1500 h
----------	--------

### Capabilities

Burning position	h45
Connection with cable	Yes
Mains terminals	Leads w/female flat connectors

### Country specific categorizations

Order reference	64333
-----------------	-------

## Product datasheet

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4008321166340   4055462135223
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321166340	OSR64333A4015	-	-	-
4008321166340	OSR64333A4015	-	-	-