



# Halogen reflector

## 6834FO 100W GZ6.35 12V 1CT/10X5F

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

#### Product data

General Information		
Cap-Base	GZ6.35 [ GZ6.35]	
Philips Code	6834FO	
ANSI Code	EFP	
LIF Code	A1/231	
Operating Position	P90/P15	
Main Application	Projection	
Life to 50% Failures (Nom)	50 h	
J Code	-	
Light Technical		
Correlated Color Temperature (Nom)	3330 K	
Color Rendering Index (Nom)	100	
Operating and Electrical		
Power (Rated) (Nom)	100 W	

Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	-
Bulb Material	Quartz-UV Open
Reflector Finish	-
Filament Shape	-
Filament Dimensions WxH	-
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	400 °C


Datasheet, 2017, September 24 data subject to change

# Halogen reflector

Working Distance WD	32 mm
Product Data	
Full product code	871150040973760
Order product name	6834FO 100W GZ6.35 12V 1CT/10X5F
EAN/UPC - Product	8711500409737
Order code	924048417104

Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	50	
Material Nr. (12NC)	924048417104	
Net Weight (Piece)	0.023 kg	

## Dimensional drawing



Product	D (max)	C (max)
6834FO 100W GZ6.35 12V 1CT/10X5F	50 mm	42 mm

