

# PRODUCT DATASHEET

## HALOSTAR PRO 14 W 12 V G4

HALOSTAR® PRO | Low-voltage halogen lamps with pin base



### Areas of application

- General illumination
- Kitchen lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

### Product benefits

- Brilliant accent lighting
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- High luminous efficacy compared with standard lamps
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

### Product features

- Average life: 4,000 h
- 100 % dimmable



- Color rendering index R<sub>a</sub>: 100
- IRC technology


## TECHNICAL DATA

## Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	20 W
Nominal current	1.67 A

## Photometrical data

Luminous flux	220 lm
Luminous efficacy	14 lm/W
Light color (designation)	Warm White
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028
UV protection	Yes



## Light technical data

Starting time	0.0 s
---------------	-------

## Dimensions &amp; Weight

Overall length	33.00 mm
Light center length (LCL)	22.0 mm
Diameter	10,0 mm
Product weight	1.1 g

## Lifespan

Lifespan	4000 h
----------	--------

Number of switching cycles	50000
<b>Additional product data</b>	
Base (standard designation)	G4
Mercury-free	Yes
<b>Capabilities</b>	
Dimmable	Yes
Burning position	Any
<b>Certificates &amp; Standards</b>	
Energy efficiency class	G
Energy consumption	15.00 kWh/1000h
<b>Country-specific categorizations</b>	
ILCOS	HSGT/C/UBIB-14-12-G4-10/22
Order reference	64423 ECO
<b>Energy labelling regulation data acc EU 2019/2015</b>	
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G4
Connected light source (CLS)	No
Color-tunable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	33.00 mm
Height	10,0 mm
Width	10,0 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.409
Beam angle correspondence	SPHERE_360
EPREL ID	714429

Model number	AC35317,AC35317
--------------	-----------------

## DOWNLOAD DATA

### DOWNLOAD DATA



CAD data 3-dim



CAD data 3-dim

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321317964	Folding box 1	70 mm x 23 mm x 25 mm	3.67 g	0.04 dm <sup>3</sup>
4008321317971	Shipping box 40	144 mm x 119 mm x 121 mm	190.00 g	2.07 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.