

# EFN 64615 HLX



#### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

### Technical data

### General product information

Product Number	54126	
Product Name	EFN64615HLX 12V 20/CS 1/SKU	
Ordering Abbreviation	EFN 64615 HLX	
Brand Name	OSRAM	
Family Brand Name	XENOPHOT (HLX)	
General Description	75 watt, tungsten halogen, low to medium voltage with reflector	
Application	Projector - 8mm	
LIF Code	A1/230	
Product Remark	– p (Operating Position) = Horizontal	

### **Electrical data**

Nominal Wattage	75 W
Nominal Voltage	12 V
Type of Current	AC

# Light technical data

Working Distance a (in)	1.260 in
Working Distance a (mm)	32 mm
Average Rated Life	50 h

## Physical attributes

Base	GZ6.35 Bipin
Bulb Shape	MR16
Maximum Overall Length (in)	1.653 in
Maximum Overall Length (mm)	42 mm
Length l (in)	1.653 in
Length l (mm)	42 mm
Length l max. (in)	1.653 in
Length l max. (mm)	42 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	C-8
Reflector Coating	51.00

### Additional product data

# Product datasheet

Operating Position	p 90/15
Class	C (gas)



#### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54126	4050300006796	Folding box (SKU)	1	1.8 in x 1.8 in x 2.3 in	0.1 lb
54126	4050300665528	Shipping box (Case)	20	9.4 in x 4.8 in x 4.2 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.