

PRODUCT DATASHEET L 36 W/76

OSRAM NATURA® T8 | Tubular fluorescent lamps 26 mm, with G13 bases, for food presentation



Areas of application

- Presentation of food in the display counter
- Especially suitable for the food sector (DIN 10504)

Product benefits

- Specially tailored spectral distribution for food presentation only



TECHNICAL DATA

Electrical data

| Nominal wattage | 36 W | |
|-----------------|--------|--|
| Nominal voltage | 103 V | |
| Nominal current | 0,43 A | |

Photometrical data

| Luminous flux | 1800 lm |
|---------------------------|---------|
| Luminous efficacy | 47 lm/W |
| Light color (designation) | NATURA |
| Color temperature | 3500 К |
| Light color | 35 |
| Rated LLMF at _2,000 h | 0.88 |
| Rated LLMF at 4,000 h | 0.83 |
| Rated LLMF at 6,000 h | 0.80 |
| Rated LLMF at 8,000 h | 0.77 |
| Rated LLMF at 12,000 h | 0.74 |
| Rated LLMF at 16,000 h | 0.72 |
| Rated LLMF at 20,000 h | 0.70 |

Dimensions & Weight

| Construction length [PICOS] | 1213.60 mm | |
|---|------------|--|
| Length | 1213.60 mm | |
| Length with base excl. base pins/connection | 1200 mm | |
| Diameter | 26,00 mm | |
| Tube diameter | 26 mm | |
| Product weight | 165,00 g | |

Lifespan

| Nominal life time | 20000 h |
|--|-----------------------|
| Service life | 13000 h ¹⁾ |
| | 0.99 |
| Rated lamp survival factor at 4,000 | 0.99 |
| Rated lamp survival factor at 6, | 0.99 |
| Rated lamp survival factor at 8,000 | 0.99 |
| Rated lamp survival factor at 12,000 h | 0.99 |

| Rated lamp survival factor at 16,000 | 0.90 |
|--|---------|
| Rated lamp survival factor at 20,000 h | 0.50 |
| Lifespan B50 | 20000 h |

1) With preheat ECG

Additional product data

| Base (standard designation) | G13 | |
|---|--------------------------|--|
| Lamp mercury content | 5.3 mg | |
| Design / version OSRAM NATURA® T8 tubular, G13 base | | |
| Product remark | Not for general lighting | |

Certificates & Standards

| Energy consumption | 39.00 kWh/1000h |
|--------------------|-----------------|
|--------------------|-----------------|

Country-specific categorizations

| ILCOS | FD-36/76-E-G13-26/1200 |
|-----------------|------------------------|
| Order reference | L 36W/76 |

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| | DOWNLOAD DATA |
|-----|----------------------------|
| POF | Certificates |
| PDF | Certificates |
| PDF | Declarations of conformity |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300010526 | Sleeves 1 | 1,215 mm x 29 mm x 29 mm | 190.00 g | 1.02 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4008321145673 | Shipping box 10 | 1,244 mm x 64 mm x 150 mm | 1765.33 g | 11.94 dm³ |
| 4050300240817 | Shipping box 25 | 1,242 mm x 142 mm x 145 mm | 5125.00 g | 25.57 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.